

SAFETY DATA SHEET

Gauged Porcelain Tile Panels/Slabs

Edition 6 – 3 March 2023

Printing date: 3 March 2023

1. Product Identification

Common Name: Gauged Porcelain Tile Panels/Slabs
brand EMILGROUP, EMILCERAMICA, ERGON, LEVEL, PROVENZA, VIVA
Use: Floor and wall coverings
Manufacturer: Emilceramica S.R.L. a socio unico
Via Ghiarola Nuova, 29 41042 Fiorano M.se (Mo) - Italy
Tel.+39 0536 835111
ambiente@emilceramicagroup.it
Emergency assistance: +39 0536 835111
Reference Health, Safety and Environment Manager

2. Hazards identification

2.1 Hazard classification as required by dir. CE 1272/2008:

not classified

2.2 Labelling as required by dir. CE 1272/2008:

not subject to hazard labelling

2.3 Other hazards:

The finished product is odorless, non-flammable, do not release hazardous materials after installation, and pose no immediate hazard to health and environment.

Hazard components as required by dir. 67/548/CE and reg. 1272/2008/CE or with occupational exposure limits are associated only to airborne particulates present into the dust produced by dry-cutting product during installation or by any other operations, including demolition/removal projects.

Hazard Statements:

H350 May cause cancer (inhalation)

H335 May cause respiratory irritation

H372 Causes damage to organs (lung/respiratory) through prolonged or repeated exposure (inhalation)

3. Composition/information on ingredients

Tile slabs are mixtures of predominately Clays, Sands, Feldspar and other naturally-occurring mineral, that have been mixed with water and fired in a very high temperature kiln (> 1200°C - >2190°F)

Tile slabs are manufactured in various shapes, sizes, and colors. These products do not contain asbestos. Under normal condition these products do not release hazardous materials after installation and are not considered hazardous waste should disposal be necessary.

Composition	CAS number	Estimated % by Wt/Wt
Silica amorphous	7631-86-9	70 - 80
Crystalline silica as QUARTZ	14808-60-7	10 – 15
Mullite	1302-93-8	2.5 - 5
Plagioclase (Feldspar)	68476-25-5	1.5 – 4.5
K-Feldspar	68476-25-5	0 – 0.5
Corundum	1302-74-5	0 – 2.5
Zirconium Silicate	10101-52-7	0 – 2.5

4. First aid measures

Description of first aid measures

Following skin contact: Wash with plenty of soap and water.

Following eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if irritation persists.

Following inhalation: Take the patient outdoors and keep them warm and still.

Most important symptoms and effects, both acute and delayed

During the floor installation process, cutting stage may produce breathable crystalline silica. Prolonged and/or large-scale inhalation of breathable crystalline silica dust may cause pulmonary fibrosis, commonly known as silicosis. The main symptoms of silicosis are coughing and shortness of breath. Occupational exposure to breathable crystalline silica dust must be monitored and controlled.

Indication of any immediate medical attention and special treatment needed

Treatment: None

5. Firefighting measures

Flash point (Method Used):	Not Applicable
Flammable limits:	Not Applicable
Autoignition Temperature:	Not Applicable
Fire Extinguishing Media:	None Required – Non Flammable
Special Fire Fighting Procedures:	None required
Fire and Exposition hazards:	None required

6. Accidental release measures

Avoid creating excessive dust. Clean up dust with a vacuum system with a High-efficiency particulate (HEPA) air filter vacuum or damp sweeping. See Section 8 of this SDS concerning PPE information for clean-up.

7. Handling and storage

When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. **Use wet cutting methods to reduce generation of dust.** Use respiratory protection in the absence of effective engineering controls.

Do not store near acids. If tile slabs contact some acids, damage/discoloration to the surface may occur. Shelf life is unlimited.

8. Exposure controls/personal protection

Control parameters (ACGH), consult national regulations if any:

Total dust (TLV/TWA)	
TLV TWA - 10 mg/m ³	
TLV STEL - n.d.	
Breathable Dust fraction (TLV-TWA)	
TLV TWA - 3 mg/m ³	
TLV STEL - n.d.	
Crystalline Sylica as QUARTZ – Brethable fraction:	
TLV TWA - 0.1 mg/m ³	
TLV STEL - n.d.	

Exposure controls

Ventilation: Use adequate ventilation to keep exposure to dust below recommended exposure levels. Avoid inhalation of dust. The highest probability of silica exposure occurs during installation using dry cutting methods or during removal of installed tile slab. **Wet cutting methods are recommended.**

Eye protection: Not required for normal use. In the absence of effective engineering controls, se dust-proof goggles or safety glasses with side shields. Contact lenses may absorb irritants. Do not wear contact lenses in work areas.

Hand/Skin protection: When cutting this product, cotton or leather work gloves should be worn to minimize skin exposure to dust and/or cuts. Wash hands prior to eating, drinking, or smoking, and at the end of the work shift, after cutting operations are conducted.

Respiratory protection: In the event of exposure levels higher than those stated in point 8.1, wearing a respiratory protection device compliant with national legal requirements is mandatory. Use of proper PPE it is still always recommended during tile slabs cutting, grinding and removing stages.

9. Physical and chemical properties

Appearance and colour:	brittle solid, color may vary
Odour:	odourless
Melting point/freezing point:	N.A. (> 2200°F)
Initial boiling point and boiling range:	N.A.
Flammability (solid/gas):	not flammable
Upper/lower flammability or explosive limit:	N.A.
Vapour density:	N.A.
Flash point:	N.A.
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Solubility in water:	insoluble

Specific Gravity (H2O = 1)	> 2
Solubility in oil:	N.A.
Partition coefficient: n-octanol/water:	N.A.
Auto-ignition temperature:	not self-inflammatory
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosive properties:	N.A.
Oxidising properties:	N.A.
Volatility:	0 g/L Volatile Organic Comp.(VOCs)

10. Stability and reactivity

Reactivity :	Inert
Chemical stability:	Stable in normal conditions
Conditions to avoid:	Contact with acid
Stability:	Stable in normal conditions
Incompatible materials:	Acid (e.g. hydrofluoridric)
Hazardous decomp. products:	None
Hazardous Polymerization:	None

11. Toxicological information

No toxicological effects are associated with intact tile slabs. The following data refer to the BREATHABLE CRYSTALLINE SILICA that is generated during cutting and demolition activities:

acute toxicity	data are missing or insufficient
skin corrosion / irritation	missing or insufficient
eye Injury / irritation:	missing or insufficient
sensitization of skin or respiratory tract:	missing or insufficient
mutagenicity:	missing or insufficient
carcinogenicity:	CATEGORY 1A
toxicity for reproduction:	missing or insufficient
specific target organ toxicity (STOT) — single exposure:	CATEGORY 3 Respiratory tract irritation
specific target organ toxicity (STOT) — repeated exposure:	CATEGORY 1A respiratory effects (pulmonary fibrosis, silicosis)
inhalation hazard:	missing or insufficient

Effects on health:

The repeated and prolonged inhalation of fine dust of crystalline silica at or above allowable occupational exposure limits may lead to the development of silicosis (a nodular pulmonary fibrosis), and are associated with pulmonary tuberculosis, bronchitis, emphysema, and other airway diseases.

This type of exposure may also be related to the development of autoimmune disorders, chronic renal disease, and other adverse health effects.

Recent epidemiologic studies demonstrate that workers exposed to elevated silica concentrations have a significant risk of developing chronic silicosis. Signs such as labored breathing and early fatigue may indicate silicosis; however, these symptoms can arise from many other causes.

Silicosis may be complicated by severe mycobacterial or fungal infections and result in tuberculosis (TB). Epidemiologic studies have established that silicosis is a risk factor for developing TB. Any existing respiratory or pulmonary diseases may be complicated by exposure to breathable crystalline silica. Smoking may increase the risk of adverse effects if done in conjunction with occupational exposure to. Breathable crystalline silica is classified by the International Agency for Research on Cancer (IARC) as a Group I Carcinogen (carcinogenic to humans). The National Toxicology Program (9th Report) lists breathable crystalline silica as Known to be a Human Carcinogen. USDOL/OSHA and NIOSH have recommended that crystalline silica be considered a potential occupational carcinogen. Short term experimental studies of rats have found that intratracheal instillation of quartz particles leads to the formation of discrete silicotic nodules in rats, mice and hamsters.

Oral (silica) Lethality
LD50 Rat oral >22,500 mg/kg
LD50 Mouse oral >15,000 mg/kg
LC50 Carp >10,000 mg/l (per 72 hr)

12. Ecological information

Toxicity: Adopt good working practices and do not discharge the product into the environment.

Persistence and degradability : N.A.
Bioaccumulative potential : N.A.
Mobility in soil : N.A.
Other adverse effects : None

13. Disposal considerations

Tile slabs are building materials. Waste treatment methods: Recover if possible or dispose in a certified landfill authorized to accept such material in accordance with the relevant local and national legislation.

14. Transport information

D.O.T Shipping Name: Not applicable
Hazard Class: Non-regulated
(for disposal purposes material is non-hazardous Class III regulated material)
ID Number: Not applicable
Marking: Not applicable
Label: None
Placard: None
Hazardous Substance/RQ: Not applicable
Packaging References: None

15. Regulatory information

15.1. Specific rules on health, safety and environment related to the product:

Regulation (EU) n. 1907/2006 (REACH):

- SVHC art. 57 (Candidate List): Not applicable
- Authorization (Annex XIV): Not applicable
- Restrictions (Annex XVII): Not applicable

Regulation (EU) n. 1272/2008 (CLP): Not applicable

Dir 2012/18/EU – control of major-accident hazards (SEVESO): Not applicable

This product contains <1 percent by weight each of the following elements, which are SARA 313 Recordable: Antimony, Arsenic, Barium, Beryllium, Cadmium, Cobalt, Chromium, Copper, Manganese, Mercury, Nickel, Lead, Silver, Thallium, Tin, Titanium, Vanadium, and Zinc.

Title 22 Division 2, California Code of Regulation Chapter 3 (Proposition 65): This product contains a chemical or chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

This product or its components meets the following hazard definition(s) as defined by the Occupational Safety and Health Hazard Communication Standard (29 CFR Section 1910.1200):

Combustible Liquid	Flammable Aerosol	Oxidizer
Compressed Gas	Explosive	Pyrophoric
Flammable Gas	X Health Hazard (Sections 3 & 11)	Unstable
Flammable Liquid	Organic Peroxide	Water Reactive
Flammable Solid		

Based on information presently available, this product does not meet any of the hazard definitions of 29 CFR Section 1910.1200.

Note: The information in this data sheet provides information related to the potential hazards associated with dusts which may be produced during cutting or otherwise changing the shape of the tile slab during installation and/or removal.

15.2. Chemical safety assessment: Not applicable

16. Other information

This document has been prepared in accordance with the Occupational Safety and Health Administration (OSHA) Hazard Communication standard, 29 Code of Federal Regulations (CFR) 1910.1200(g), Safety Data Sheets.

According with REACH (Registration, Evaluation, Authorisation and Restriction of Chemicals – EU Regulation 18/12/2006), tile slabs are classified as “ARTICLE: object with physical properties more important to its function than any chemical properties” so that, a SDS is not required/mandatory. Nevertheless, this SDS also complies with CLP Regulation EC1272/2008 (CLP).

This SDS has been prepared with the best knowledge and based on the information sources currently available.

Users' attention is also drawn to the possible risks connected to a use of the product other than that for which it was designed.

This data sheet replaces and cancels any previous version.

Abbreviations and Acronyms:

N.A. not applicable - not available

LD50: Lethal dose for 50 percent of the test population.

LC50: Lethal concentration for 50 percent of the test population.

TLV: Threshold limit value.

TWA: Time weighted average

STEL: Short-term exposure limit.

STOT: Organ-specific toxicity

Complete text about hazard statement in section 2:

(H350) May cause cancer (inhalation)

(H335) May cause respiratory irritation

(H372) Causes damage to organs (lung/respiratory) through prolonged or repeated exposure (inhalation)