

STONE PROJECT



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: ULCDM/CG UL 2818

FALDA

SAND



WHITE



GREIGE



GREY



BLACK



STRUTTURATO

FORMATI

Sizes | Formats | Formate | Tamaños | Форматы

9,5 mm.

60x120 - 23^{5/8}"x47^{1/4}" Naturale R10 - Lappato - Strutturato R11

60x60 - 23^{5/8}"x23^{5/8}" Naturale R10

30x60 - 11^{13/16}"x23^{5/8}" Naturale R10 - Strutturato R11

SUPERFICI

Finishes | Finitions | Oberflächen | Superficies | Отделка поверхности

NATURALE

R10 DIN EN 16165 Annex B

B (A+B) DIN EN 16165 Annex A

Wet \geq 0,50 DCOF

> 0,40 B.C.R.A.

P2 Pendolo AS 4586

< 36 Moderate Slip potential - Slider 96 Pendolo BS 7976

- Pendolo UNE 41901

LAPPATO

- DIN EN 16165 Annex B

- DIN EN 16165 Annex A

- DCOF

- B.C.R.A.

- Pendolo AS 4586

- Pendolo BS 7976

- Pendolo UNE 41901

STRUTTURATO

R11 DIN EN 16165 Annex B

C (A+B+C) DIN EN 16165 Annex A

Wet \geq 0,65 DCOF

> 0,40 B.C.R.A.

P3 Pendolo AS 4586

> 36 Low Slip potential - Both sliders Pendolo BS 7976

3 Pendolo UNE 41901

SHADE VARIATIONS



V3 HIGH

DESTINAZIONI D'USO

Intended uses | Domaines d'application
Zweckbestimmung | Usos previstos | Назначение



放射線水平線



15% 9,5 mm
valori medi - average values



White 20x120

STONE PROJECT

COLORI E FORMATI

Colours and Sizes | Couleurs et Formats | Farben und Formate | Colores y Tamaños | Цвета и Форматы

Sand Falda | Strutturato R11



White Falda | Strutturato R11



Greige Falda | Strutturato R11



Si consiglia la posa con fuga 2 mm. - Laying with a 2 mm-joint is recommended. - Pose recommandée avec joints de 2 mm.
 Es wird eine Fugenbreite von 2 mm empfohlen. - Se recomienda la colocación con juntas de 2 mm. - Рекомендуется укладка с швом 2 мм.
 Verificare l'abbinamento dei toni tra i formati differenti. - Check the colour matching between different sizes.
 Vérifier l'assortiment des tonalités entre les différents formats. - Die Kombination der Farbtöne unter den verschiedenen Formaten prüfen.
 Comprobar la combinación de los tonos entre los distintos formatos. - Проверьте сочетание тонов у разных форматов.

STONE PROJECT

COLORI E FORMATI

Colours and Sizes | Couleurs et Formats | Farben und Formate | Colores y Tamaños | Цвета и Форматы

FALDA



Naturale R10 Rett.
 60x120 - 23^{5/8}"x47^{1/4}"
E7RK Sand ● T31
E6L3 White ● T31
E7RM Greige ● T31

Strutturato R11 Rett.
 60x120 - 23^{5/8}"x47^{1/4}"
E7RQ Sand ● T31
E4VD White ● T31
E7RR Greige ● T31

Lappato Rett.
 60x120 - 23^{5/8}"x47^{1/4}"
E6L2 White ● T49



Naturale R10 Rett.
 60x60 - 23^{5/8}"x23^{5/8}"
E37Y Sand ● T17
E1E4 White ● T17
E380 Greige ● T17



Naturale R10 Rett.
 30x60 - 11^{13/16}"x23^{5/8}"
E38A Sand ● T14
E1DD White ● T14
E38D Greige ● T14

Strutturato R11 Rett.
 30x60 - 11^{13/16}"x23^{5/8}"
E38G Sand ● T14
E1DL White ● T14
E38H Greige ● T14

IMBALLI E PESI

Packing and Weight | Emballages et Poids | Verpackung und Gewicht | Embalajes y Pesos | Упаковка и Вес

Formato Size Format Format Тamaño Формат см	Spessore Thickness Epaisseur Stärke Espesor Толщина мм	Pz. x Mq. Pieces x Sqm Pcs / M ² Stk. x Qm Pzs x Mc. Шт x Кв.М.	Pz. x Scat. Pieces x Box Pcs / Bte Stk. x Krt. Pzs x Caja Шт x Кор.	Mq. x Scat. Sqm x Box M ² / Bte Qm x Krt. Mc. x Caja Кв.М. x Кор.	Peso x Scat. Weight x Box Poids / Bte Gewicht x Krt. Peso x Caja Вес x Кор. Kg	Scat. x Pal. Boxes x Pal. Bte / Pal. Krt. x Pal. Cajas x Pal. Кор. x Подд.	Mq. x Pal. Sqm x Pal. M ² / Pal. Qm x Pal. Mc. x Pal. Кв.М x Подд.	Peso x Pal. Weight x Pal. Poids / Pal. Gewicht x Pal. Peso x Pal. Вес x Подд. Kg
60x120 Naturale R10 - Lappato - Strutturato R11	9,5	1,39	2	1,440	31,68	36	51,84	1140
60x60 Naturale R10	9,5	2,78	3	1,080	23,76	40	43,20	950
30x60 Naturale R10 - Strutturato R11	9,5	5,56	6	1,080	23,76	48	51,84	1140
30x30 Mosaico Naturale R10	9,5	11,11	5	0,450	8,73	60	27,00	524

STONE PROJECT

COLORI E FORMATI

Colours and Sizes | Couleurs et Formats | Farben und Formate | Colores y Tamaños | Цвета и Форматы

Grey Falda | Strutturato R11



Black Falda | Strutturato R11



FALDA

9,5 mm.



Naturale R10 Rett.
60x120 - 23^{5/8}"x47^{1/4}"
E1CK Grey ● T31
E6L8 Black ● T31

Strutturato R11 Rett.
60x120 - 23^{5/8}"x47^{1/4}"
E6LA Grey ● T31
E6LC Black ● T31



Naturale R10 Rett.
60x60 - 23^{5/8}"x23^{5/8}"
E1E8 Grey ● T17
E1EA Black ● T17



Naturale R10 Rett.
30x60 - 11^{13/16}"x23^{5/8}"
E1DH Grey ● T14
E1DK Black ● T14

Strutturato R11 Rett.
30x60 - 11^{13/16}"x23^{5/8}"
E1DN Grey ● T14
E1DP Black ● T14

Si consiglia la posa con fuga 2 mm. - Laying with a 2 mm-joint is recommended. - Pose recommandée avec joints de 2 mm.
Es wird eine Fugenbreite von 2 mm empfohlen. - Se recomienda la colocación con juntas de 2 mm. - Рекомендуется укладка с швом 2 мм.
Verificare l'abbinamento dei toni tra i formati differenti. - Check the colour matching between different sizes.
Vérifier l'assortiment des tonalités entre les différents formats. - Die Kombination der Farbtöne unter den verschiedenen Formaten prüfen.
Comprobar la combinación de los tonos entre los distintos formatos. - Проверьте сочетание тонов у разных форматов.


STONE PROJECT

DECORI

Decors | Decors | Dekore | Decorados | Декоры

MOSAICO FALDA* Naturale R10


Tessera - Chip 4,8x4,8 - 1^{7/8}"x1^{7/8}"



30x30 - 11^{13/16}"x11^{13/16}"
E39K Sand ● A96



30x30 - 11^{13/16}"x11^{13/16}"
E1ES White ● A96



30x30 - 11^{13/16}"x11^{13/16}"
E39L Greige ● A96



30x30 - 11^{13/16}"x11^{13/16}"
E1EU Grey ● A96



30x30 - 11^{13/16}"x11^{13/16}"
E1EV Black ● A96

* Su rete in fibra - On fibre mesh backing - Sur filet en fibre de verre - Auf Glasfasernetz - Sobre malla de fibra - На волоконной сетке

PEZZI SPECIALI

Trims | Pieces Speciales | Formteile | Piezas Especiales | Специальные Изделия

	Dimensione Size						Fascia di prezzo Price band
 Gradino - Stair Tread	Naturale R10 Rett. 33x60 - 12 ^{15/16} "x23 ^{5/8} " Pcs. Box. 6 - LM x Box 3,60	E9KP	E1F6	E9KQ	E7Z3	E7Z4	● A54
	Strutturato R11 Rett. 30x33 - 11 ^{13/16} "x12 ^{15/16} " Pcs. Box. 9 - LM x Box 2,70	E9KW	E7ZU	E9KX	E7ZW	E7ZX	● A29
 Gradone - Step	Naturale R10 Rett. 33x60x3,2x3,2 12 ^{15/16} "x23 ^{5/8} "x1 ^{1/4} "x1 ^{1/4} " Pcs. Box. 4 - LM x Box 2,40	E9KF	E2E0	E9KH	E8Q4	E8Q6	● A68
 Angolare Dx Sx Corner Tile Right Left	Naturale R10 Rett. 33x33x3,2x3,2 12 ^{15/16} "x12 ^{15/16} "x1 ^{1/4} "x1 ^{1/4} " Pcs. Box. 2 - LM x Box 0,66	Dx - Right E9JP	Dx - Right E2DX	Dx - Right E9JT	Dx - Right E8PA	Dx - Right E8PF	● A72
		Sx - Left E9JQ	Sx - Left E8P3	Sx - Left E9JU	Sx - Left E8PC	Sx - Left E8PG	
 Elemento a "L" L Shaped Piece	Strutturato R11 Rett. 15x60x4,5 5 ^{7/8} "x23 ^{5/8} "x1 ^{3/4} " Pcs. Box 4 - LM x Box 2,40	E7Z5	E3AC	E3AD	E1FN	E1FP	● A34
 Cove Base*	Naturale R10 16x30 - 6 ^{5/16} "x11 ^{13/16} " Pcs. Box 30	E9LY	E1FJ	E9LZ	E1FL	E1FM	● A22
 Cove Base Ang. Int.* Cove Base In Corner	Naturale R10 2,5x16 - 1 ^{5/16} "x6 ^{5/16} " Pcs. Box 10	E9LD	E1EN	E9LE	E1EQ	E1ER	● A16
 Cove Base Ang. Est.* Cove Base Out Corner	Naturale R10 2,5x16 - 1 ^{5/16} "x6 ^{5/16} " Pcs. Box 10	E9LA	E1EJ	E9LC	E1EL	E1EM	● A16

* Ordine minimo 500 pezzi - Minimum order: 500 pieces - Commande minimale 500 pièces
Mindestbestellmenge 500 Stücke - Pedido mínimo 500 piezas - Минимальный заказ - 500 штук

I pezzi speciali inclusi nel campo di applicazione della EN 14411:2016 presentano le stesse caratteristiche di superficie dei fondi di partenza.
Trims within the scope of EN 14411:2016 have the same surface characteristics as the relative plain tiles.

STONE PROJECT

Dry - Pressed Ceramic Tiles ISO 13006 Annex G - UNI EN 14411 Annex G - Bia UGL



CARATTERISTICHE TECNICHE

Technical Features - Caracteristiques Techniques - Technische Eigenschaften
Tecnische Eigenschaften - Características Técnicas - Технические Характеристики

NORMA

Standard - Norme
Norm - Norma - Норма

VALORI

Value - Valeur
Vorgabe - Valor - Средние

	ASSORBIMENTO D'ACQUA (VALORE MEDIO IN %) Water absorption (Average value expressed in %) - Absorption d'eau (Valeur moyenne en %) Wasseraufnahme (Durchschnittswert in %) - Absorción de agua (Valor medio en %) Поглощение воды	UNI EN ISO 10545/3 ≤ 0,5 %	CONFORME		
		ASTM C373	COMPLIANT		
	RESISTENZA ALLA FLESSIONE Modulus of rupture - Resistance a la flexion - Biegefestigkeit Resistencia a la flexion - Прочность на изгиб	UNI EN ISO 10545/4	≥ 50 N/mm ²		
		ASTM C648	400 Lbs		
	RESISTENZA AL GELO Frost resistance - Résistance au gel - Frostbeständigkeit Resistencia a las heladas - Морозостойкость	UNI EN ISO 10545/12	CONFORME		
		ASTM C1026	UNAFFECTED		
	RESISTENZA CHIMICA AD ALTE E BASSE CONCENTRAZIONI DI ACIDI E BASI Chemical resistance to high and low acid and basic concentrations Résistance chimique aux hautes et basses concentrations d'acides et de bases Chemikalienfestigkeit bei hohen und niedrigen Konzentrationen von Säuren und Basen Resistencia química con concentraciones altas y bajas de ácidos y bases Химическая стойкость к высоким и низким концентрациям кислот и щелочей	UNI EN ISO 10545/13	A - LA - HA		
		ASTM C-650	UNAFFECTED		
	RESISTENZA ALLE MACCHIE Stain resistance - Résistance aux taches - Fleckenbeständigkeit Resistencia a las manchas - Стойкость к образованию пятен	UNI EN ISO 10545/14	5		
		CTI 81-7D	NO EVIDENT VARIATION		
	COEFFICIENTE DI ATTRITO Slip resistance - Coefficient de glissement - Rutschfestigkeit Barfußbereich Coeficiente de atrito medio - Коэффициент трения		NAT.	LAPP.	STRUTT.
		DIN 51130	R10	R9	R11
		DIN 51097	B (A+B)	A	C (A+B+C)
		ANSI A 137.1- 2012 DCOF (SECTION 9.6)	WET ≥ 0,50	WET ≥ 0,42	WET ≥ 0,65
		B.C.R.A.	≥ 0,40	≥ 0,40	≥ 0,40
		AS 4586: 2013 Slip resistance classification of new pedestrian surface materials	P2	-	P4
		BS 7976-2: 2002 Pendulum testers	< 36 Moderate Slip Potential	-	> 36 Low Slip Potential
ENV 12633-2006 Method of determination of unpolished and polished slip/skid resistance value	-	-	3		

Per maggiori chiarimenti sui dati tecnici e sulla garanzia consultare il catalogo generale in vigore. - For further information on technical specifications, please consult our up-dated general catalogue. - Pour toutes informations supplémentaires sur les données techniques et sur les garanties, veuillez consulter le catalogue général en vigueur. - Für weitere Informationen über technische Daten und Garantie beziehen sie sich bitte auf den aktuellen Gesamtkatalog. - Para ultérieures informaciones sobre los datos técnicos y la garantía, vease el catalogo general en vigor. - Более подробную информацию о технических данных и гарантии смотрите в действующем сводном катал.




PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL.COM/GG UL 2818



放射性水平A类



Min. 7,5%



Formato Size Format Format Tamaño Формат cm	Spessore Thickness Epaisseur Stärke Espesor Толщина mm	Pz. x Mq. Pieces x Sqm Pcs / M ² Stk. x Qm Pzs x Mc. Шт x Кв.М.	Pz. x Scat. Pieces x Box Pcs / Bte Stk. x Krt. Pzs x Caja Шт x Кор.	Mq. x Scat. Sqm x Box M ² / Bte Qm x Krt. Mc. x Caja Кв.М. x Кор.	Peso x Scat. Weight x Box Poids / Bte Gewicht x Krt. Peso x Caja Вес x Кор. Kg	Scat. x Pal. Boxes x Pal. Bte / Pal. Krt. x Pal. Cajas x Pal. Кор. x Подд.	Mq. x Pal. Sqm x Pal. M ² / Pal. Qm x Pal. Mc. x Pal. Кв.М x Подд.	Peso x Pal. Weight x Pal. Poids / Pal. Gewicht x Pal. Peso x Pal. Вес x Подд. Kg
60x120 Naturale - Lappato - Strutturato	10	1,39	2	1,440	32,86	36	51,84	1183
20x120 Naturale - Lappato	10	4,17	4	0,960	21,85	40	38,40	874
60x60 Naturale - Lappato	10	2,78	3	1,080	24,50	40	43,20	980
30x60 Naturale - Lappato - Strutturato	10	5,56	6	1,080	24,74	40	43,20	990
30x30 Mosaico	10	11,11	5	0,450	9,75	60	27,00	585
30x60 Listelli sfalsati	10	5,56	4	0,720	16,00	30	21,60	480



A Brand of Emileramica S.r.l. a socio unico

